

ad notam®

HIDDEN TECHNOLOGY - TECHNOLOGY BECOMES INVISIBLE.

DFU-0420-875

ACCESSORIES

MONITOR




ad notam

DFU-0420-875



55 kWh/1000h



2019/1013

PACKAGE INCLUDES

- 1x DFU Monitor System
- 1x External Power Adaptor
- 1x AC Power Cord
- 1x IR Remote Control Waterproof incl. Batteries
- 1x User Manual



Proprietary and Confidential The information contained in this document is the sole property of ad notam.

Any reproduction in part or in whole without written permission from ad notam is prohibited.

This product, parts, components or the assembly might be part of or protected by one of the following intellectual property rights:

EP 1168285 / US 7,455,412 / EP 1429308 / EP 1809828 / US 7,589,893 / DE 10139890

ad notam[®]

HIDDEN TECHNOLOGY - TECHNOLOGY BECOMES INVISIBLE.

MONITOR


DFU-0420-875

GENERAL INFORMATION


Article number	DFU-0420-875
Product dimensions *	1035 x 628 x 53,7 mm (40.75" x 24.72" x 2.11")
Product weight	17,8 kg (39.2 lbs)
Permitted product usage	For In-Door-Use only
Operating temperature	0 to 50 Celcius (32 to 122 Fahrenheit)
Humidity	20% - 80%
HS Code	85 28 52 91

DRAWINGS


Frontview



Sideview



Topview



Drawing measure

mm

inches

ad notam®

HIDDEN TECHNOLOGY - TECHNOLOGY BECOMES INVISIBLE.

DFU-0420-875

SPECIFICATION

Display type (Backlight type)	TFT Thin Film Transistor (LED)
Screen diagonale	42.51" (1079.75 mm)
Screen active area (WxH) **	941 x 529 mm (37.05" x 20.82")
Picture format	16:9
Physical resolution	3840 x 2160
Viewing angle	Horizontal (Total / Left / Right): 178 / 89 / 89 Vertical (Total / Up / Down): 178 / 89 / 89
Brightness ***	max. 1000 cd/m ²
Contrast	Typical: 1300:1
Response time	9 ms
Refresh rate	60 Hz
Power consumption	DC 24V / Standby: 0,5W / 21mA / Maximum: 119W / 4.96A
OSD language	Deutsch, English, Espanol, Francais, Italiano, Portugues, Chinese
Certification	EN 62368-1, EN 55032, EN 55024, EN 55013, EN 55020, EN 61000, EN 50581, EN 14372, IEC62321
Lifetime (backlight)	~ 15.000 operating hours

INPUTS & OUTPUTS

Input	Output		
X		HDMI 2.0	3x HDMI terminal 480i, 480p, 576i, 576p, 720i, 720p, 1080i, 1080p, UHD
X		Component (YPbPr / YCbCr)	3x RCA terminal green (Y), blue (Pb), red (Pr) 720p, 1080i, 1080p
X		USB	1x USB terminal Media Player & Software Update
X		RS232	1x D-Sub 9pin male
X		Line Audio Input	2x RCA terminal white (L), red (R)
X		IR Input (Infrared)	1x Mini Jack 3.5 mm
X		VGA	1x D-Sub 15pin female VGA, SVGA, XVGA, SXVGA, UXGA
X		DC Input	1x DC XLR 4pin male 24V
	X	Speaker Output	1x Phoenix Clip 4pin 2x 8W RMS @ 8 Ohms per channel
	X	IR Output (Cable)	1x Mini Jack 3.5 mm
	X	IR Output (LED)	1x Mini Jack 2.5 mm
	X	Line Audio Output	1x Mini Jack 3.5 mm
	X	DC Output 5V/12V	1x Molex Mini-Fit Jr. Header, Dual Row, 4 Circuit max. 2.0A / only one active voltage

* Tolerances of +/- 1 mm apply.

** The glass active area is always a little smaller than the specified screen active area.

*** Brightness varies at factory calibrated settings.